



office

ficha técnica

datasheet

ref. 5551967



Nombre / Name	office s/alimentación • luminaria lineal
Referencia / Reference	5551967
Materiales / Materials	Aluminio+acero+PC / Aluminum+steel+PC
Difusor / Diffuser	PC
Potencia / Power	60W
Temperatura de color / Color temperature	4000K
Flujo luminoso / Luminous flux	No
Dimable / Dimmable	97°
Ángulo de apertura / Beam angle	7039lm
Ángulo de inclinación / Inclination angle	-
IP	20
I.K.	05
F.P	>0,95
UGR	>22
IRC	>80
Chip	OSRAM
Driver	Lifud non-flicker
Vida media (duración) / Average life	50,000h
Clase energética / Energy class	F
Aislamiento eléctrico / Electrical isolation	Clase II / Class II
Colores / Colors	Negro / Black
Medida exterior / Product size	1480mm x 28mm x 68mm
Protección contra Sobretensiones / surge protection	1,5kV
Tª (ambiente/trabajo) / Tª (enviroment/work)	-25°C~45°C
Input	AC200~240V
Output	DC80~200V
Frecuencia / Frequency	50/60Hz
Peso / Weight	1,5kg
Certificados / Certificates	CE&RoHS
Garantia / Warranty	2 años / 2 years