



tira led 5050

ficha técnica

datasheet

ref.5550202



Nombre / Name	tira led 5050
Referencia / Reference	5550202
Materiales / Materials	Cobre + Plástico / Copper + Plastic
LED / mt	120led/mt
Potencia / Power	125W (25W/mt)
Temperatura de color / Color temperature	6500K
Flujo luminoso / Luminous flux	13800lm (2760lm/mt)
Dimable / Dimmable	Opcional / Optional
Ángulo de apertura / Beam angle	120°
Ángulo de inclinación / Inclination angle	-
IP	65
IK	-
F.P	-
UGR	-
IRC	>75
Chip	EPISTAR SMD 5050
Driver	-
Vida media (duración) / Average life	± 40,000h
Clase energética / Energy class	-
Aislamiento eléctrico / Electrical isolation	-
Colores / Colors	Blanco / White
Medida exterior / Product size	5mts x 16mm
Medidas de corte / Cutting measurements	Cada 50mm / every 50mm
Tª (ambiente/trabajo) / Tª (environment/work)	-20°C ~ 45°C
Input	-
Output	DC24V
Frecuencia / Frequency	50/60Hz
Peso / Weight	225grs rollo / 225grs roll
Certificados / Certificates	CE RoHS
Garantia / Warranty	2 años / 2 years